

Product data sheet

E guide rail Boxer



With lever and electric hold-open device

AREAS OF APPLICATION

- Single leaf doors
- Integrated installation
- Hold-open systems with integrated hold-open device
- Right and left single-action doors

E guide rail Boxer



PRODUCT FEATURES

- Operating voltage 24 V DC
- Retention force of the electromechanical hold-open device can be variably adjusted
- With screwed slide block

TECHNICAL DATA

Productname	E guide rail Boxer
Input voltage	24 V DC
Electrical power consumption	1 W
Duty rating	100 %
Residual ripple	20 %
IP rating	IP43
Standard conformity	EN 1155
Length	440 mm
Width	31 mm
Height	30 mm
Hold-open function	Electrical
Hold-open device can be switched on and off	Yes
Hold-open device can be overridden	Yes
Hold-open range	80 ° - 120 °
Smoke switch integrated	No
Flexible opening restrictor	Yes

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Dimensions	Colour	Hold-open point min.
E guide rail Boxer	With lever and electric hold-open device	119640	440 x 31 x 30 mm	silver-coloured	80 °
E guide rail Boxer	With lever and electric hold-open device	135775	440 x 31 x 30 mm	according to RAL	80 °

E guide rail Boxer



ACCESSORIES

FLEXIBLE OPENING RESTRICTOR

For E and R guide rails, single and double leaf



Designation	Description	Ident-No.
Flexible opening restrictor	for guide rail 1-leaf: TS 5000 E/R/RFS (door leaf installation), Boxer E; 2-leaf: all E/R/ISM variants TS 5000 (incl. VPK) and Boxer	145311